LED LINEAR HIGHBAY





Housing Die-cast aluminum

Light Source Lumiled

Benefits Easy installation

Low maintenance required

Increase energy efficiency Improved lighting quality

More compact, unique

DESCRIPTION

Warebay Linear Highbay series are designed to replace the industry highbay lighting fixture, using superior LED chip solution and pure aluminum heat sink enables the luminous efficacy higher to 130 lm/w with excellent thermal management.

APPLICATION

Factories, Steel Mills, Steel Smelting Plants, Farms, sport Facilities & Workshops, Storage Facilities & Warehouses, Supermarkets & Department Stores, Showrooms, Design Centers & Galleries.

SPECIFICATION

	35-WAREBAY HBL	35-WAREBAY HBL	35-WAREBAY HBL	35-WAREBAY HBL 200W	
	50W	100W	150W		
LED Chip	Lumiled	Lumiled	Lumiled	Lumiled	
LED Driver	Meanwell	Meanwell	Meanwell	Meanwell	
Wattage	50W	100W	150W	200W	
Lumen@Source*	6500 lm	13000 lm	19500 lm	26000 lm	
CCT**	3000K / 4000K / 5000K / 5700K				
Beam Angle	30x70° / 60x100° / 120°				
CRI (Ra)	>80	>80	>80	>80	
LED Life	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	
Working Ambient Temperature	50°C	50°C	50°C	50°C	


*Luminous Flux tolerance ±5% / **CCT Tolerance ±5%

Data is subject to change without notice




LED LINEAR HIGHBAY






SCHEMATIC



ORDERING GUIDE

35-WAREBAY HBL-50	830	840	850	857	50W
35-WAREBAY HBL-100	830	840	850	857	100W
35-WAREBAY HBL-150	830	840	850	857	150W
35-WAREBAY HBL-200	830	840	850	857	200W

ORDERING EXAMPLE



Data is subject to change without notice