

32-905COB

LED SPOTLIGHT



- Housing** Die-cast aluminum
- Reflector** Aluminum
- Diffuser** Semi-frosted PC
- Light Source** COB LED
- Benefits**
 - Breakthrough system cost
 - Good quality and light performance
 - Easy to install



DESCRIPTION

A recessed mounted, cost-effective, integrated LED spotlight module with good quality of light that's easy to suit any application.

APPLICATION


Can be used in a wide range of applications from Residential to Commercial spaces.

SPECIFICATION

	32-905COB 8W	32-905COB 10W	32-905COB 12W
LED Chip	Samsung	Samsung	Samsung
LED Driver	Philips	Philips	Philips
Wattage	8W	10W	12W
Lumen@Source*	1040 lm	1300 lm	1560 lm
Beam Angle	36°	36°	36°
CCT**	3000K / 4000K / 6500K	3000K / 4000K / 6500K	3000K / 4000K / 6500K
CRI (Ra)	>80 and 3 SDCM	>80 and 3 SDCM	>80 and 3 SDCM
LED Life	50,000 hrs / L70	50,000 hrs / L70	50,000 hrs / L70
Working Ambient Temperature	50°C	50°C	50°C

*Luminous Flux tolerance ±5% / **CCT Tolerance ±5%


Data is subject to change without notice.



ADDITIONAL OPTIONS

- DALI Digital Dimming
- EL3 Emergency Kit - 3 hrs


SCHEMATIC



ORDERING GUIDE

32-905COB-8-830	8W	32-905COB-10-830	10W	32-905COB-12-830	12W
32-905COB-8-840	8W	32-905COB-10-840	10W	32-905COB-12-840	12W
32-905COB-8-865	8W	32-905COB-10-865	10W	32-905COB-12-865	12W

ORDERING EXAMPLE



LED SPOTLIGHT 905COB-10-830/IP44