




36-LTNEONFLEX 1010

LED FLEXIBLE STRIPLIGHT



Material	Silicon
Features	- UV resistant - Waterproof - Dirt resistant - Easy to install - Durable - Sets the mood - Variety of uses - Available in various lamp colors such as Red, Green, Blue, and Amber



Aluminum profile accessory available as an option

DESCRIPTION

LED flexible strip lights are reliable, cost-effective way to add extra light in any places you need. Because of its excellent choice for functionality, it can be used in various applications such as an accent light or as a decorative lighting solution which would also enhances the mood for the area.

APPLICATION


Mostly use in facade areas.

SPECIFICATION


	36-LTNF-1010 4.8W	36-LTNF-1010 9.6W
LED Chip	SMD LED 2835	SMD LED 2835
Supply Voltage	24V DC	24V DC
LED Quantity	120 pcs / mtr	120 pcs / mtr
Wattage	4.8W / mtr	9.6W / mtr
Beam Angle	120°	120°
Lumen	80 lm/W	80 lm/W
CCT**	3000K / 4000K / 6500K	3000K / 4000K / 6500K
CRI (Ra)	>80	>80
LED Life	50,000 hrs	50,000 hrs
Min. Cutting Length	50 mm	50 mm
Working Ambient Temperature	50°C	50°C

*Luminous Flux tolerance ±5% / **CCT Tolerance ±5%

Data is subject to change without notice.





SCHEMATIC



Dimensions are in mm

POLAR DIAGRAM



ADDITIONAL OPTIONS

- ☐ DALI Digital Dimming
- ☐ FP Flexible profile
- ☐ M/F Male female IP Connector

ORDERING GUIDE

36-LTNF-1010-4.8-830	4.8W	36-LTNF-1010-9.6-830	9.6W
36-LTNF-1010-4.8-840	4.8W	36-LTNF-1010-9.6-840	9.6W
36-LTNF-1010-4.8-865	4.8W	36-LTNF-1010-9.6-865	9.6W

ORDERING EXAMPLE

36-LTNF-1010-4.8-830/IP67					
36	LTNF	1010	4.8	830	IP67
LED Flexible Striplight	Family Name	Model	Wattage	CRI & CCT	IP Rating

LED FLEXIBLE STRIPLIGHT LTNEONFLEX-1010-4.8-830/IP67

- *Please mention side bend or top bend required while placing an order.
- *Please mention single end or double end connection required while placing an order.
- *Conector entry position to be mentioned (Front/Back/Side)
- *Pigtail cable standard length is 0.3 mtr. Extra length options available at additional cost.